

TECHNOSONUS BAND

GOST 5763-001-81846463-2010
TNVED 6807100009

DESCRIPTION

TechnoSonus Band is a thin elastic bitumen-based band of high strength, with adhesive layer on one side. It is designed for adhering and hermetic sealing of butt joints in soundproofing with bituminous rolled sound insulation materials.

COMPOSITION

- bitumen-polymer base;
- protective film;
- adhesive layer.



SIZE AND WEIGHT

Modifications	Length, mm	Width, mm	Thickness, mm	Roll Area, m ²
TechnoSonus band	15000	35	1,3	0,525

SPECIFICATIONS

Parameter	TechnoSonus Band
Waterproofing Capacity at 0.2 MPa during 2 hrs	absolute
Force at Rupture, N	70
Surface Density, kg/m ²	1,9

APPLICATION

- Adhering butt joints of bituminous insulation materials of all types.
- Metal pipe corrosion prevention.

FEATURES

- Multipurpose usefulness: is suitable for rooms of all types and purposes.
- Usability: is suitable for all bitumen-based heat-, sound-, and water insulation materials.
- High waterproofing and soundproofing performance.
- Excellent adhesion to various materials.
- Good elasticity, flexibility.
- User friendliness: easy to cut, quick and effective fixation.
- Adhesive layer.
- Resistance to biological impact and to damage by fungus, insect pests.

CERTIFICATES

1. GOST R Certificate of Conformity.

PACKAGING AND TRANSPORTATION

Modifications	Package	Roll Area, m ²	Roll Weight, kg	Roll Volume, m ³	82 m ³ Euro Trailer Loading Capacity, pcs.
TechnoSonus Band	roll	0,525	1	0,0008	22000

The products are delivered in rolls. The products shall be stored away from sources of heat and UV radiation in a dry place at max. 35°C.